


FORM PTO-1390 (REV 12-29-99)		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE		ATTORNEY'S DOCKET NUMBER 12394/1	
<b>TRANSMITTAL LETTER TO THE UNITED STATES          DESIGNATED/ELECTED OFFICE (DO/EO/US)          CONCERNING A FILING UNDER 35 U.S.C. 371</b>				U.S. APPLICATION NO. (If known, see 37 CFR 1.5) <div style="font-size: 24pt; font-weight: bold;">10/069398</div>	
INTERNATIONAL APPLICATION NO. PCT/JP00/05137		INTERNATIONAL FILING DATE July 28, 2000		PRIORITY DATE CLAIMED August 26, 1999	
TITLE OF INVENTION ENERGY ABSORBING TYPE STEERING DEVICE, AND METHOD AND DEVICE FOR ASSEMBLING THE STEERING DEVICE					
APPLICANT(S) FOR DO/EO/US SHIOYA, Shigemi; SADATO, Kita; SHIMADA, Takashi; SANO, Seiji					
<p>Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:</p> <ol style="list-style-type: none"> <li>1. <input checked="" type="checkbox"/> This is a <b>FIRST</b> submission of items concerning a filing under 35 U.S.C. 371.</li> <li>2. <input type="checkbox"/> This is a <b>SECOND</b> or <b>SUBSEQUENT</b> submission of items concerning a filing under 35 U.S.C. 371.</li> <li>3. <input checked="" type="checkbox"/> This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).</li> <li>4. <input checked="" type="checkbox"/> A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.</li> <li>5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371(c)(2))             <ol style="list-style-type: none"> <li>a. <input type="checkbox"/> is transmitted herewith (required only if not transmitted by the International Bureau).</li> <li>b. <input checked="" type="checkbox"/> has been transmitted by the International Bureau.</li> <li>c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US).</li> </ol> </li> <li>6. <input checked="" type="checkbox"/> A translation of the International Application into English (35 U.S.C. 371(c)(2)).</li> <li>7. <input checked="" type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))             <ol style="list-style-type: none"> <li>a. <input type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau).</li> <li>b. <input type="checkbox"/> have been transmitted by the International Bureau.</li> <li>c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired.</li> <li>d. <input checked="" type="checkbox"/> have not been made and will not be made.</li> </ol> </li> <li>8. <input type="checkbox"/> A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).</li> <li>9. <input type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).</li> <li>10. <input type="checkbox"/> A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).</li> </ol> <p><b>Items 11. to 16. below concern document(s) or information included:</b></p> <ol style="list-style-type: none"> <li>11. <input type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98.</li> <li>12. <input type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.</li> <li>13. <input checked="" type="checkbox"/> A <b>FIRST</b> preliminary amendment.  <input type="checkbox"/> A <b>SECOND</b> or <b>SUBSEQUENT</b> preliminary amendment.</li> <li>14. <input type="checkbox"/> A substitute specification.</li> <li>15. <input type="checkbox"/> A change of power of attorney and/or address letter.</li> <li>16. <input type="checkbox"/> Other items or information:</li> </ol>					

U.S. APPLICATION NO. (if known) <b>10/069398</b> INTERNATIONAL APPLICATION NO. <b>PCT/JO00/03900</b>		ATTORNEY'S DOCKET NUMBER <b>960/124</b>	
17. <input checked="" type="checkbox"/> The following fees are submitted: <b>BASIC NATIONAL FEE ( 37 CFR 1.492 (a) (1) - (5) ) :</b> Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO ..... <b>\$970.00</b> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO ..... <b>\$840.00</b> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO ..... <b>\$690.00</b> International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4) ..... <b>\$670.00</b> International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4) ..... <b>\$96.00</b> <b>ENTER APPROPRIATE BASIC FEE AMOUNT =</b>		<b>CALCULATIONS</b> PTO USE ONLY	
Surcharge of <b>\$130.00</b> for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).		<b>\$ 890.00</b>	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE
Total claims	26    - 20 =	6	X <b>\$18.00</b>
Independent claims	3    - 3 =	0	X <b>\$78.00</b>
MULTIPLE DEPENDENT CLAIM(S) (if applicable)			+ <b>\$260.00</b>
<b>TOTAL OF ABOVE CALCULATIONS =</b>		<b>\$ 998.00</b>	
Reduction of 1/2 for filing by small entity, if applicable. A Small Entity Statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28).		<b>\$</b>	
<b>SUBTOTAL =</b>		<b>\$ 998.00</b>	
Processing fee of <b>\$130.00</b> for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).		<b>\$ -0-</b>	
<b>TOTAL NATIONAL FEE =</b>		<b>\$ 998.00</b>	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). <b>\$40.00</b> per property		<b>\$ 0.00</b>	
<b>TOTAL FEES ENCLOSED =</b>		<b>\$ 998.00</b>	
<b>Amount to be refunded:</b>		<b>\$</b>	
<b>charged:</b>		<b>\$</b>	
a. <input type="checkbox"/> A check in the amount of \$_____ to cover the above fees is enclosed.  b. <input checked="" type="checkbox"/> Please charge my Deposit Account No. <u>11-0600</u> in the amount of \$ <u>998</u> to cover the above fees. A duplicate copy of this sheet is enclosed. c. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. <u>11-0600</u> . A duplicate copy of this sheet is enclosed.			
<b>NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.</b>			
SEND ALL CORRESPONDENCE TO: John C. Altmiller KENYON & KENYON 1500 K Street, N.W., Suite 700 Washington, DC 20005  Tel.: (202) 220-4200 Fax: (202) 220-4201		 SIGNATURE: John C. Altmiller  NAME 25,951  REGISTRATION NUMBER	

PATENT

Docket No.: 12394/1

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

APPLICANTS : Shigemi SHIOYA et al.  
SERIAL NO. : (Nat'l. Phase of PCT/JP00/05137)  
FILED : 26 February 2002  
FOR : ENERGY ABSORBING TYPE STEERING DEVICE, AND  
METHOD AND DEVICE FOR ASSEMBLING THE  
STEERING DEVICE

ASSISTANT COMMISSIONER  
FOR PATENTS  
Washington, D.C. 20231

**PRELIMINARY AMENDMENT**

SIR:

Prior to examination of this national phase application, please enter the following amendments.

**In the Specification:**

Please amend the specification as follows:

Page 12, line 22: Change "BEST MODE FOR PRACTICING THE INVENTION" to  
-- DETAILED DESCRIPTION --

**In the Abstract:**

Please replace the Abstract with the following new Abstract:

-- Energy absorbing steering devices may include an outer cylindrical member (OU) that is press-fitted around an inner shaft member (IN). The outer shape of the inner shaft member and the inner shape of the outer cylindrical member have a circular cross-section and the diameter of the inner shape of the outer cylinder member is larger than the diameter of the outer shape of the inner shaft member. A plurality of fine members (W) is disposed along the axial direction between the circular cross-sectional outer shape and the circular cross-sectional inner shape in

order to provide a clearance (G) between the inner shaft member and the outer cylindrical member. The arrangement of the fine members may be modified in order to adjust the rigidity of relative movement along the axial direction of the outer cylindrical member and the inner shaft member. —

**In the Claims:**

Please cancel claims 1-15 and enter the following new claims:

16. An apparatus for absorbing energy comprising:

an inner shaft member having an outer surface that is circular in cross-section,

an outer cylindrical member press-fitted around the inner shaft member, the outer cylindrical member having an inner surface that is circular in cross-section and the diameter of the inner surface of the outer cylindrical member is larger than the diameter of the outer surface of the inner shaft member, and

a plurality of fine members interleaved between the outer cylindrical member and the inner shaft member, the fine members extending along a straight line along an axial direction of the inner shaft member and the outer cylinder member.

17. An apparatus as in claim 16, wherein the fine members have a Vickers hardness and either (1) the inner shaft member has a Vickers hardness that differs by at least 200 from the Vickers hardness of the fine members or (2) the outer cylindrical member has a Vickers hardness that differs by at least 200 from the Vickers hardness of the fine members.

18. An apparatus as in claim 16, wherein the plurality of fine members are arranged to require a pre-determined pressing load in order for the outer cylindrical member to axially displace relative to the inner shaft member.

19. An apparatus as in claim 16, wherein an axially extending clearance is defined between the inner shaft member and the outer cylindrical member and proximal to the fine members.

20. An apparatus as in claim 16, wherein the length of the fine members along the axial direction is longer than or equal to a predetermined length that ensures a clearance between the inner shaft member and the outer cylindrical member when the inner shaft member and the outer cylindrical member absorb energy and become more deeply fitted.

21. An apparatus as in claim 16, further comprising means for preventing movement of the fine members in the axial direction.

22. An apparatus as in claim 16, wherein the fine members further comprise a coupling portion that fixedly couples the fine members to an end face of the inner shaft member or to an end face of the outer cylindrical member.

23. An apparatus as in claim 22, further comprising means for preventing the coupling portions of the fine members from dislodging from the end face of the inner shaft member or the end face of the outer cylindrical member.

24. An apparatus as in claim 23, wherein the fine members have a Vickers hardness and either (1) the inner shaft member has a Vickers hardness that differs by at least 200 from the Vickers hardness of the fine members or (2) the outer cylindrical member has a Vickers hardness that differs by at least 200 from the Vickers hardness of the fine members.

25. An apparatus as in claim 24, wherein the length of the fine members along the axial direction is longer than or equal to a predetermined length that ensures a clearance between the inner shaft member and the outer cylindrical member when the inner shaft member and the outer cylindrical member absorb energy and become more deeply fitted.

26. An apparatus as in claim 16, wherein the inner shaft member is an inner tube or an inner shaft and the outer cylindrical member is an outer tube or an outer shaft.

27. A method for assembling a steering device comprising:

extending a plurality of fine members along the axial direction of an outer surface of an inner shaft member or an inner surface of an outer cylindrical member, and

press-fitting the outer cylindrical member around the inner shaft member, wherein the fine members are disposed within a clearance defined between the inner shaft member and the outer cylindrical member at least along the length of the fine members that are interleaved between the inner shaft member and the outer cylindrical member.

28. A method as in claim 27, wherein during the press-fitting step, at least one of the inner shaft member, the outer cylindrical member, or the fine members is deformed beyond an elastic limit thereof.

29. A method as in claim 27, further comprising during the press-fitting step: measuring the pressing load being applied, and cutting the fine members when the measured pressing load reaches a predetermined value.

30. A method as in claim 29, wherein during the press-fitting step, at least one of the inner shaft member, the outer cylindrical member, or the fine members is deformed beyond an elastic limit thereof.

31. A method as in claim 27, wherein a predetermined length of the plurality of fine members is extended along the axial direction of the inner shape of the outer cylindrical member, and the inner shaft member is press-fitted while preventing the fine members from being axially pulled further into the outer cylindrical member.

32. A method as in claim 31, wherein during the press-fitting step, at least one of the inner shaft member, the outer cylindrical member, or the fine members is deformed beyond an elastic limit thereof.

33. An apparatus for assembling a steering device comprising:

means for extending a plurality of fine members along the axial direction of an outer surface of an inner shaft member or an inner surface of an outer cylindrical member, and

means for press-fitting the outer cylindrical member around the inner shaft member, wherein the fine members are disposed within a clearance defined between the inner shaft member and the outer cylindrical member at least along the length of the fine members that are interleaved between the inner shaft member and the outer cylindrical member.

34. An apparatus as in claim 33, further comprising means for deforming at least one of the inner shaft member, the outer cylindrical member, or the fine members beyond an elastic limit thereof.

35. An apparatus as in claim 33, further comprising:

means for measuring the pressing load being applied by the pressing means, and

means for cutting the fine members when the measured pressing load reaches a predetermined value.

36. An apparatus as in claim 33, wherein the extending means extend a predetermined length of the plurality of fine members along the axial direction of the inner shaft of the outer cylindrical member, and the press-fitting means prevent the fine members from being axially pulled further into the outer cylindrical member.

37. An apparatus as in claim 16, wherein the movement of the fine members in the axial direction is prohibited with respect to one of the inner shaft member and outer cylindrical member and is allowed with respect to the other of the inner shaft member and outer cylindrical member.

38. An apparatus as in claim 16, wherein the cross-section of each fine member is circular.

39. An apparatus as in claim 16, wherein each fine member is made of steel wire.

40. An apparatus as in claim 16, wherein each fine member is made of steel wire having a property such that the rigidity is increased when bent.

41. An apparatus as in claim 33, further comprising a drum for winding fine members, wherein wound fine members are pulled from the drum while press-fitting the inner shaft member into the outer cylindrical member.

2007-10-26 09:00:00




**REMARKS**

The specification has been amended to change a sub-title to U.S. format.  
Claims 1-15 have been deleted and a new Abstract has been provided.

Examination in light of these amendments is respectfully requested.

The Office is hereby authorized to charge any additional fees under 37 C.F.R.  
§ 1.16 or § 1.17 or credit any overpayment to Deposit Account No. 11-0600.

Respectfully submitted,

  
John C. Altmiller  
(Reg. No. 25,951)

Dated: 26 February 2002

KENYON & KENYON  
1500 K Street, N.W., Suite 700  
Washington, D.C. 20005-1257

Tel: (202) 220-4200  
Fax: (202) 220-4201

17/pvt

ENERGY ABSORBING TYPE STEERING DEVICE AND METHODS AND  
APPARATUS FOR ASSEMBLING THE STEERING DEVICE

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to techniques for readily producing steering devices having uniform energy absorption performance. Herein, 'uniform' means that variations (in energy absorption performance) from product to product are small.

Description of the Related Art

Known energy absorbing type steering devices include a cylindrical steering tube (often referred to as a column) that surrounds a steering shaft. The steering tube is formed by fitting an inner tube into an outer tube. If energy is applied to the steering shaft, the tubes become more deeply fitted in order to absorb the energy. Another known absorbing type steering device includes a steering shaft. The steering shaft is formed by fitting an inner shaft into an outer shaft. The shafts become more deeply fitted when energy is absorbed. In yet another known energy absorbing type steering device, a steering tube is attached to a vehicle body so as to be axially displaceable. In response to energy being applied to the steering shaft, the steering tube is displaced relative to the vehicle body in order to absorb the energy.

All the above-described energy absorbing type steering devices absorb energy applied to the steering shaft by allowing the inner shaft member, which is fitted within the outer cylindrical member, to axially displace

relative to the outer cylindrical member.

In a steering tube formed from an inner tube and an outer tube, the outer tube serves as an outer cylindrical member and the inner tube serves as an inner shaft member. In a steering shaft formed from an inner shaft and an outer shaft, the outer shaft serves as an outer cylindrical member and the inner shaft serves as an inner shaft member. In a structure in which a displaceable steering tube is attached to a vehicle body, an outer cylindrical member secured to a bracket that is affixed to the vehicle body serves as an outer cylindrical member. In this case, the steering tube serves as an inner shaft member.

During the manufacture of such energy absorbing type steering devices, variations in energy absorption performance from product to product within the same lot must be very small.

Japanese Unexamined Patent Publication No. 56-8755 and Japanese Unexamined Utility Model Publication No. 56-6669 disclose techniques that address the above-described requirement. These references describe an energy absorption steering device, in which an inner shaft is pressed into an outer shaft and a fine member, such as a piano wire, is interleaved between the shafts, thereby minimizing variations in energy absorption performance from product to product.

In a steering shaft, the rigidity of outer and inner shafts should not be too great along the axial direction in order to provide the required energy absorption performance; however, the rigidity thereof should be sufficiently great in the rotating direction in order to prevent the shafts from rotating relative to each other.

In order to satisfy these requirements, the above-described prior art steering devices ensure satisfactory transmission of torque by pressing an inner shaft having an oval cross section into an outer shaft having inner shape whose cross section is similar to the shape of the inner shaft. These prior art steering devices dispose a single piano wire between the shafts in order to prevent the axial rigidity from varying between products.

In the above-described prior art steering devices, the oval cross section of the shaft ensures the transmission of the required torque. However, the inner shaft and the outer shaft contact at least at one point in the cross section. Therefore, energy absorption performance is directly affected by differences in the finish of the outer surface of inner shaft and the inner surface of outer shaft and by the dimensional tolerances of these components. Thus, realization of uniform energy absorption performance is hindered.

A steering tube made of an inner tube and an outer tube also has the same problem. Differences in the finish of the outer surface of inner tube and the inner surface of outer tube, and the dimensional tolerances of the components, directly cause variations in energy absorption performance and impede uniform energy absorption performance.

In a structure in which a displaceable steering tube is attached to a vehicle body, direct contact of an outer cylindrical member that is fixed to the vehicle body via a bracket, and the steering tube results in large variations in energy absorption performance. In order to achieve uniform energy absorption performance, as shown in Japanese

Unexamined Patent Publication No. 8-20348, a cylindrical spacer made of a rigid synthetic resin is interleaved between the steering tube and the outer cylindrical member. Thus, a special spacer must be provided to impart uniform performance.

Accordingly, it is an object of the present invention to realize techniques that significantly decrease the effect of differences in the tolerances of components and variations in the finishes thereof on energy absorbing performance as compared to prior art techniques, and more specifically, to realize techniques for setting the energy absorption performance of each product at a predetermined constant level, even if the tolerances of the components and variations in the finishes thereof differ between products. It is another object of the present invention to provide such structures at a relatively low cost.

#### DISCLOSURE OF THE INVENTION

Energy absorbing type steering devices according to the present invention are characterized in that an inner shaft member is press-fitted into an outer cylindrical member, the inner shaft member having a circular cross-sectional outer shape and the outer cylindrical member having a circular cross-sectional inner shape that is larger in diameter than the inner shaft member; and, a plurality of fine members is disposed between the circular cross-sectional outer shape and the circular cross-sectional inner shape such that the fine members extend along the axial direction of the members.

According the above description, pressing the inner shaft member into the outer cylindrical member also means

pressing the outer cylindrical member around the inner shaft member. Both pressing operations are equivalent and generate the same result.

In the steering devices of the present invention, because a plurality of fine members is disposed between the inner shaft member and the outer cylindrical member, the dimensional tolerances of the inner shaft member and outer cylindrical member and variations in the surface conditions of the members have little effect on energy absorption performance and thus, a robust technique is achieved.

By experimentation, the inventors confirmed that by interleaving a plurality of fine members between the inner shaft member and the outer cylindrical member, both of which have circular cross-sections and thus can easily rotate relative to each other, the inner shaft member can be press-fitted within the outer cylindrical member rigidly in the rotating direction and less rigidly along the axial direction so that appropriate energy absorption performance is ensured. A single fine member disposed between the shaft member and the cylindrical member does not provide the same results as a plurality of fine members. That is, pressing the circular cross-sectional inner shaft member into the circular cross-sectional outer cylindrical member with a single fine member interleaved therebetween, while maintaining the appropriate rigidity in the axial direction, decreases rigidity in the rotating direction. Thus, sufficient torque transmission is not provided. In order to overcome this problem, prior art cylinders and shafts have utilized an oval cross-sectional shape, as shown in Japanese Unexamined Patent Publication No. 56-8755 and Japanese Unexamined Utility Model Publication No 56-

6669.

Energy absorbing type steering devices according to the present invention provide energy absorption performance that does not vary from device to device. In addition, the inner shaft member and the outer cylindrical member of each steering device are fitted together rigidly in the rotating direction and less rigidly in the axial direction to an appropriate degree. Further, the steering device is manufactured from circular cross-sectional members and fine members at a relatively low cost.

By applying the present invention to a steering shaft, an inner shaft can be press-fitted within an outer shaft in a manner that reliably ensures transmission of torque from one shaft to the other shaft. Therefore, rotational slippage does not occur. Moreover, by applying the invention to a steering column, the inter tube and outer tube are prevented from rotating relative to each other, which would hinder subsequent assembly steps. If the steering device according to the present invention is utilized between an outer cylindrical member, which is secured to a bracket that is affixed to a vehicle body, and a steering tube, the fitted together steering tube and outer cylindrical member are prevented from rotating relative to each other, which would make it difficult to perform subsequent assembly steps.

In the axial direction of an energy absorbing type steering device, each fine member is preferably longer than or equal to a length that ensures a clearance between the inner shaft member and the outer cylindrical member when the steering device is absorbing energy, which occurs when the inner shaft member is being pressed more deeply into

the outer cylindrical member.

When this requirement is satisfied, uniform energy absorption performance, or energy absorption, is achieved when the inner shaft member axially displaces relative to the outer cylindrical member.

In addition, the difference in Vickers hardness between the inner shaft member and each fine member or between the outer cylindrical member and each fine member is preferably at least 200. It does not matter whether the Vickers hardness of fine member is greater or less than the inner shaft member and the outer cylindrical member.

This requirement ensures plastic deformation of the inner shaft member and outer cylindrical member or plastic deformation of the fine members when the inner shaft member is press-fitted into the outer cylindrical member. Accordingly, uniform energy absorption performance is ensured regardless of the manufacturing tolerances of the members.

The positions of fine members are preferably selected in accordance with the pressing load that is required to press-fit the inner shaft member within the outer cylindrical member.

For example, when four fine members are disposed at regular intervals (i.e., at ninety-degree intervals about the center of the inner shaft member), the inner shaft member is fitted into the outer cylindrical member so as to ensure high axial rigidity. On the other hand, when two pairs of spaced apart fine members are disposed such that the angle about the center of the inner shaft member is divided, e.g., into 60 degrees, 120 degrees, 60 degrees, and 120 degrees, the inner shaft member is fitted within



the outer shaft member so that low axial rigidity is ensured.

That is, by changing the circumferential arrangement of the fine members, steering devices having different energy absorption performances can be produced using the same members. Accordingly, energy absorbing type steering devices can be produced by changing the circumferential arrangement of the fine members in accordance with the pressing load that is required to press-fit the inner shaft member into the outer cylindrical member.

Further, the fine members preferably are fixedly coupled to an end face of the inner shaft member or the outer cylindrical member in order to prevent movement of the fine members in the axial direction.

When this requirement is satisfied, the inner shaft member is securely press-fitted within the outer cylindrical member with the fine members disposed between the members. Also, when energy is applied to the steering device and the inner shaft member becomes more deeply fitted into the outer cylindrical member, the fine members are maintained at a constant axial position with respect to either the inner shaft member or the outer cylindrical member, thereby ensuring uniform energy absorption performance when energy is absorbed.

A pull-in prevention means is preferably provided at a coupling portion of each fine member and the coupling portion is attached to the end face of the inner shaft member or the outer cylindrical member. For example, the pull-in prevention means may include a loop in the fine member that prevents the coupling portion from being pulled into the clearance between the inner shaft member and the

outer cylindrical member.

Because the pull-in prevention means prevents the coupling portion from being pulled into the clearance, energy absorption performance becomes substantially uniform.

The present invention also provides innovative methods for assembling energy absorbing type steering devices. Methods for assembling energy absorbing type steering devices, in which an inner shaft member is press-fitted into an outer cylindrical member, are characterized by a step of extending a plurality of fine members in the axial direction along the outer shape of the inner shaft member or along the inner shape of the outer cylindrical member and a step of press-fitting the inner shaft member into the outer cylindrical member with the fine members disposed between the inner shaft member and the outer cylindrical member so that the fine members provide a clearance between both members.

This method facilitates assembly of steering devices having uniform energy absorption performance.

In the above-described assembling method, at least one of the inner shaft member, the outer cylindrical member, or the fine members preferably deforms beyond the respective elastic limit thereof. When one deforms past its elastic limit, or is plastically deformed, the adverse effects of dimensional tolerances of the members decrease, which provides an extremely uniform energy absorption performance.

In this method, the load that is applied to press-fit the inner shaft member into the outer tube member preferably is measured and the fine members are preferably

cut when the measured load reaches a predetermined value.

Thus, by using this method, steering devices can be reliably assembled so as to have an energy absorption performance that is adjusted to a predetermined value.

In the alternative, according to this method, a predetermined length of the fine members may preferably be axially positioned along the inner shape of the outer cylindrical member and the inner shaft member may preferably be press-fitted into the outer cylindrical member while preventing the fine members from being axially drawn into the outer cylindrical member.

By using this method, the lengths of the fine members disposed between the shaft member and the cylindrical member can be accurately determined and steering devices that provide uniform energy absorption performance can be more easily assembled.

The present invention further provides innovative apparatus for assembling steering devices. The assembling apparatus includes a device that press-fits an inner shaft member into an outer cylindrical member and a fine-member supply device that supplies a plurality of fine members to the clearance between the outer shape of the inner shaft member and the inner shape of the outer cylindrical member. The fine-member supply device is disposed adjacent to the press-fitting device.

According to this apparatus, steering devices having uniform energy absorption performance are easily and efficiently assembled.

In this apparatus, the fine-member supply device preferably can be adjusted with respect to the circumferential direction of the inner shaft member and

outer cylindrical member. Such an apparatus enables the production of energy absorbing type steering devices having various levels of rigidity with respect to the axial direction.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 schematically shows a steering tube according to one embodiment of the present invention.

Fig. 2 is a cross-sectional view taken along line II-II shown in Fig. 1.

Figs. 3(A), (B), and (C) show fine members before and after the steering tube is assembled.

Fig. 4 is a graph showing a relationship between material deformation and load.

Fig 5 shows an assembling apparatus according to a first embodiment.

Fig. 6 is a cross-sectional view of a fitted portion of a steering tube assembled by the apparatus of Fig. 5.

Fig. 7 is a cross-sectional view taken along line VII-VII in Fig. 6.

Fig. 8 shows an assembling apparatus according to a second embodiment.

Fig. 9 is a cross-sectional view of a fitted portion of a steering tube assembled by the apparatus of Fig. 8.

Fig. 10 shows a bending mechanism incorporated into the apparatus of Fig. 8.

Fig. 11 is a graph showing a relationship between pressing depth and load.

Fig. 12 shows an assembling apparatus according to a third embodiment.

Fig. 13 is a graph showing a relationship between

pressing depth and load.

Fig. 14 shows examples of fine members.

Fig. 15 shows examples of the cross section of the fine members.

Figs. 16(A) and (B) show two examples of the fine members.

Figs. 17(A), (B), (C), and (D) show another two examples of the fine members.

Figs. 18(A), (B), (C), (D) and (E) show further examples of the fine members.

Figs. 19(A), (B), (C), (D), (E), and (F) show further examples of fine members.

Figs. 20(A), (B), (C), (D), (E), (F), and (G) show further examples of fine members.

Figs. 21(A), (B), (C), and (D) show the relationship between the fine members and the end face of the tube.

Figs. 22(A), (B), (C), (D), (E), and (F) show the relationships between different arrangements of the fine members and axial rigidity.

Figs. 23(A), (B), (C), (D), (E), and (F) show examples of different arrangements of the fine members.

#### BEST MODE FOR PRACTICING THE INVENTION

Embodiments according to the present invention will hereinafter be described with reference to the accompanying drawings. Figs. 1 and 2 schematically show the positional relationship of inner tube IN fitted within outer tube OU. The outer shape of inner tube IN has a circular cross section and the inner shape of outer tube OU also has a circular cross section. The inner diameter of outer tube OU is larger than the outer diameter of inner tube IN.

When both tubes are fitted together, annular-shaped gap G is defined between tubes IN and OU. A plurality of fine members W is fitted within gap G between tubes IN and OU. The outer diameter of each of fine members W, before being fitted therein, is larger than the width of gap G, which means that fine members W are squeezed within gap G. Fine members W are disposed such that outer tube OU and inner tube IN are maintained at coaxial relationship. The number of fine members is preferably greater than or equal to three. However, two bent fine members also can be utilized to maintain inner tube IN and outer tube OU at coaxial relationship.

Fine members W are less rigid than tubes IN and OU. Each fine member W, which has a circular cross section before being fitted into the gap as shown in Figs. 3(A), is plastically deformed when fitted therein as shown in Figs. 3(B). This will become clear by referring to WS in Fig. 3(C). In the alternative, fine members W may be more rigid than tubes IN and OU, in which case the tubes will plastically deform when receiving fine members W. This will also become clear by referring to WH in Fig. 3(C). Depressions are formed within both the portion of the outer wall of tube IN and the portion of the inner wall of tube OU that contact a common fine member. Moreover, the portions adjacent to the depressions are distended.

Tubes IN and OU and fine members W may all have equal rigidity, in which case all these components will plastically deform when fitted together.

Fig. 4 shows the relationship between the load applied to each component and its deformation. When deformed beyond its elastic limit, the load becomes

constant regardless of the amount of deformation. In the present invention, because at least one of tube IN, tube OU, or fine member W is deformed beyond its elastic limit, the components are fitted together using a substantially constant load. In Fig. 4, area D indicates the range of elastic deformation. By fitting the components together within the elastic range, the fitting load varies. In the present invention, by deforming at least one of the components within the plastic deformation level indicated by area E, the dimensional tolerances of the components are prevented from varying the fitting load.

Fig. 5 shows an assembling apparatus according to the first embodiment of the present invention. First column 50B is fixed to base 50A. Jig 50C vertically positions outer tube OU and is disposed on the upper end of first column 50B. Cylinder 55C is fixed above jig 50C. Cylinder 55C is fixed to first column 50B by a member, which is not shown. Another jig 55A vertically positions inner tube IN and is disposed at the lower end of piston 55B of cylinder 55C. Outer tube OU and inner tube IN are coaxially positioned by respective jigs 50C, 55A. When jig 55A is lowered by cylinder 55C, inner tube IN is pressed into outer tube OU. In other words, outer tube OU is press-fitted around inner tube IN. In this specification, there is no difference in meaning between these two expressions.

Four fine member supply devices 60 are disposed near first column 50B. The fine member supply devices are all identical in structure. Therefore, the following description will be focused on only one.

Fine member supply device 60 includes second column 50D, which is fixed to base 50A. Arms 51A, 51B are mounted

on second column 50D via cylinders, which are not shown, so as to be selectively moved upward or downward. Fine member W is wound around drum 51D, which faces side arm 51A and freely rotates. Three fine members W1, W3, W4 are shown in the drawing and fine member W2 is blocked from view. Hereinafter, reference numerals will be omitted for the description of the common features of fine members W1, W2, W3, W4.

Wrist 51C is disposed at the upper end of arm 51B and can rotate about pin 53. A pair of fine member supply rollers 52 is rotatably mounted on wrist 51C. The pair of rollers 52 is rotated by a motor, which is not shown. Cutter 54 for cutting fine member W is attached to the lower end of wrist 51C.

The assembling apparatus includes a device that presses outer tube OU around inner tube IN. The assembling apparatus also includes a fine member supply device that supplies fine members W into a clearance defined between the outer shape of inner tube IN and the inner shape of outer tube OU and the fine member supply device is adjacent to the pressing device.

The operation of the assembling apparatus will now be described. First, outer tube OU is set on jig 50C. Then, fine member supply rollers 52 rotate a predetermined number of times so as to feed a predetermined length of fine member W. The fed fine member axially extends a predetermined length along the inner face of outer tube OU. At this time, four fine members W are circumferentially arranged in such a manner as to be equally spaced apart from each other. In this state, each of fine member supply rollers 52 is prevented from rotating. Subsequently, inner



tube IN is held by jig 55A. Thereafter, cylinder 55C is actuated in order to press down jig 55A. As a result, inner tube IN is pressed into outer tube OU and four fine members W are axially disposed the predetermined distance along the inner face of outer tube OU. At this time, inner tube IN does not directly contact outer tube OU. While inner tube IN is being pressed into outer tube OU, each of fine member supply rollers 52 is prohibited from rotating so as to prevent fine members W from being further pulled into outer tube OU.

After inner tube IN is pressed into outer tube OU, arms 51A, 51B are lowered in order to bend down fine member W, which extends from the upper face of outer tube OU. At this time, wrist 51C rotates about pin 53. Cutter 54 cuts bent fine member W at a line that is spaced by a predetermined length from the face of the upper end of outer tube OU. Then, fine member W, which extends from outer tube OU, is further bent along outer tube OU using a tool. This operation will become clear by referring to Fig. 6.

In a steering tube assembled in such a manner, outer tube OU is press-fitted around inner tube IN, four fine members W are disposed a predetermined length along the inner shape of outer tube OU and the four fine members W are prohibited from being axially pulled further into outer tube OU. Accordingly, fine member W extends between inner tube IN and outer tube OU and has been cut at a predetermined length. This feature contributes to ensuring uniform energy absorption performance. Four fine members W separate inner tube IN and outer tube OU from each other (i.e., clearance G exists in the space in which there is no

fine member W), thereby preventing inner tube IN from directly contacting outer tube OU. This feature also contributes to ensuring uniform energy absorption performance. After assembling the steering tube, fine member W remains bent and fixed to the upper end face of outer tube OU. If energy is applied to both tubes IN and OU so that inner tube IN is pressed more deeply into outer tube OU, fine members W will reliably guide inner tube IN during the pressing operation while remaining fixedly coupled to the upper end face of outer tube OU. In addition, because fine members W are fixedly coupled to the upper end face of outer tube OU and are prohibited from moving in the axial direction, the energy absorption performance is uniform when energy is being absorbed. Further, by using a sufficient length of fine member W, tubes IN and OU are maintained in a parallel relationship when inner tube IN is pressed deeply into the outer tube OU. This sufficient length also prevents both tubes from bending and thus contacting each other. This feature prevents inner tube IN from directly contacting outer tube OU when energy is absorbed. The axial length of fine member W is predetermined in order to prevent inner tube IN from directly contacting outer tube OU when inner tube IN is further pressed into outer tube OU in order to absorb energy. Accordingly, the energy absorption performance is uniform when energy is absorbed. If three or more fine members are used, the tubes can be maintained in a parallel relationship. Therefore, any number of fine members, not less than three, may be used. In addition, two bent fine members can be utilized to fit together both tubes while providing a clearance between the tubes.

Fine member W of the above-described first embodiment is a steel wire that is more rigid than the tubes. The steel wire is made rigid by being processed. In the present embodiment, each tube wall that contacts the steel wire is deformed beyond its elastic limit. One tube is pressed into the other tube within the range of plastic deformation. Therefore, even if there are variations in the sizes of tubes IN and OU, the variations impart little adverse effect on the assembling load.

The steering tube according to the present embodiment and the method for assembling steering tubes provide uniform energy absorption performance. Also, the apparatus for assembling steering tubes enables efficient assembling of steering tubes having uniform energy absorption performance.

As mentioned above, the present invention is preferably utilized at a position between the outer tube and the inner tube. However, the present invention also may be utilized at a position between an outer shaft and an inner shaft, in which case the inner shaft may be solid or tubular. The present invention can also be utilized at a position between an outer tube member of a bracket, which is affixed to a vehicle body, and a steering tube.

Fig. 8 shows an assembling apparatus according to a second embodiment of the present invention. The main body of the device is equivalent to the main body of the device shown in Fig. 5. Thus, like elements will be denoted with the same reference numerals and will not be described in detail.

In this assembling apparatus, a bending device, as shown in Fig. 10, is disposed adjacent to wrist 51C. In

Fig. 10, reference numerals 58 indicate a pair of gripping pawls, which grips the ends of the fine members, while reference numerals 57 indicate another pair of gripping pawls, which grips the fine members at a position higher than gripping pawls 58. Gripping pawls 58 are selectively turned upward or downward, as shown in Fig. 10(B). Therefore, gripping pawls 58 bend the end of fine member W. Fine member W becomes rigid due to processing. Accordingly, the bent portion is rigid.

The apparatus of Fig. 8 operates as follows. Outer tube OU is first set on jig 50C. Then, each of fine member supply rollers 52 is rotated a predetermined number of times in order to feed a predetermined length of fine member W. The fed fine member is aligned with the downward path of inner tube IN. By lowering inner tube IN, portions W1A, W2A, W3A, W4A of the ends of the respective fine members are placed into positions in which the respective portions will be fixed to the lower end face of hollow inner tube IN. In the same manner as the first embodiment, four fine members W are equally spaced apart from each other around the circumference. In this state, a motor freely permits each of fine member supply rollers 52 to rotate. Subsequently, inner tube IN is set on jig 55B. Cylinder 55C is actuated to press down jig 55B. When jig 55B is pressed down, the bent ends of the four fine members W are fixedly coupled to the lower end face of lowered inner tube IN. When inner tube IN is further lowered, fine member W is further pulled from drum 51D. Inner tube IN is further pressed down into outer tube OU with four fine members W interposed therebetween. As inner tube IN is pressed more deeply into outer tube IN, more of fine member

W is pulled from drum 51. Upon pressing inner tube IN to a predetermined depth, cylinder 55C is stopped. Cutter 54A then cuts fine member W on a line near the upper end face of outer tube OU.

In steering tubes assembled with this apparatus, fine member W extends the depth of insertion of inner tube IN into outer tube OU. Thus, direct contact of tubes IN and OU is reliably prevented. In addition, the lengths of inner tube IN and outer tube OU are predetermined so that tubes IN and OUT do not bend. This feature prevents both tubes from bending and contacting each other when the tubes are absorbing energy.

When inner tube IN is inserted more deeply, fine member W becomes fixedly coupled to the lower end of inner tube IN. Thus, fine member W is prevented from axially displacing with respect to inner tube IN, and as a result, the lower end of inner tube IN does not directly contact the inner face of outer tube OU. By fixedly coupling fine member W to the lower end face of inner tube IN, movement of fine member W in the axial direction is prohibited with respect to inner tube IN, thereby making the energy absorption performance of steering tubes assembled using this apparatus substantially uniform.

A number of experiments were conducted by the inventors, which show that the energy absorption performance can be made substantially uniform by using fine members W having a Vickers hardness that is at least 200 greater than the material of the tubes. This point will become clear by referring to Fig. 11.

In Fig. 11, the load required to press inner tube IN into outer tube OU at a constant speed is indicated by the

vertical axis while the pressing depth is indicated by the horizontal axis. The straight thick solid line indicates the results of experiments using a fine member having a Vickers hardness that is 200 greater than the tubes. The bent thin line indicates the results of experiments using a fine member having a Vickers hardness that is 100 greater than the tubes. If the Vickers hardness of the fine member is 200 greater than the tubes, the pressing load linearly increases with the pressing depth. An unsatisfactory difference in Vickers hardness between the fine member and the tubes results in an irregular relationship between the pressing load and the pressing depth. The inventors found through experimentation that control of the pressing depth ensures accurate control of the pressing load as long as the difference in Vickers hardness is at least 200.

The experiments also show that a fine member made of material having a Vickers hardness that is at least 200 less than the tube member material also ensures a linear relationship between the pressing depth and the pressing load. Accordingly, when the difference in Vickers hardness between inner tube IN and fine member W, or between outer tube OU and fine member W, is at least 200, energy absorption is extremely uniform.

The inventors conducted many other experiments that resulted in the discovery that the arrangement of fine members W has a substantial effect on the axial rigidity of the tubes. This point will become clear by referring to Fig. 22. Fig. 22(B) shows fine members W circumferentially disposed around the common center of the tubes so as to form an angle of  $15^\circ$ , an angle of  $165^\circ$ , an angle of  $15^\circ$ , and an angle of  $165^\circ$  between adjacent fine members W.

Each two fine members form a pair, and the two pairs are widely spaced apart from each other in the direction of the tube diameter. In this case, both tubes tend to be easily deformed in an oval shape when one tube is pressed into the other tube. Therefore, the axial rigidity of the fitted tubes is relatively low. As shown in the graph of Fig. 22(F), the pressing force that is required to press-fit the tubes together, or the axial load that is required to displace the fitted tubes relative to each other, is indicated by the vertical axis. The angle between each two adjacent fine members is indicated by the horizontal axis. As noted above, when the angle is  $15^\circ$ , the axial pressing load is low.

Fig. 22(E) shows the arrangement angles of the fine members as viewed from the tube center, in which the fine members are disposed at intervals of  $90^\circ$ . Thus, the four fine members are equidistantly disposed around the circumference. In this case, the tubes are each subjected to change in circumferential length when one tube is pressed into the other tube. Therefore, the axial rigidity of the assembled tubes is very high. As shown in Fig. 22(F), the axial load required to displace the fitted tubes relative to each other is very large.

Figs. 22(B) to (D) show arrangement angles that are between  $15^\circ$  and  $90^\circ$ . As the intervals between the adjacent fine members approach regular intervals, the axial load becomes larger. To the contrary, as the intervals become more irregular, the axial load becomes smaller.

This relationship enables the energy absorption properties to be changed while still using the same components. By disposing the fine members at regular

intervals, the axial load of the energy absorbing type steering tube will be large. By disposing the fine members at irregular intervals, the axial load of the energy absorbing type steering tube will be small.

Figs. 23(A) to (C) show various arrangements of three fine members. Figs. 23(D) to (F) show various arrangements of six fine members. By selecting one of these arrangements, the axial rigidity can be modified. The arrangements shown in Figs. 23 (A) and (D) provide high rigidity while the arrangements shown in Figs. 23(C) and (F) provide low rigidity.

The above-described second embodiment provides an example of using the present invention at the position between the outer tube and the inner tube. However, the present invention may be utilized at a position between an outer shaft and an inner shaft, in which case the inner shaft may be solid or tubular. The present invention can also be utilized at a position between an outer tube member of a bracket, which is affixed to a vehicle body, and a steering tube.

Fig. 12 shows an assembling apparatus according to the third embodiment of the present invention. The assembling apparatus of the present embodiment is similar to the assembling apparatus of Fig. 8. Therefore, only different features will now be discussed. In the assembling apparatus, jig 55B includes load cell 55D in order to measure the required pressing load. The assembling apparatus performs the assembly while measuring the pressing load. Fine member W is cut when the pressing load reaches a predetermined value.

Fig. 13 schematically shows the relationship between



the pressing depth and the pressing load. Reference mark A indicates the relationship between the pressing depth and the pressing load for product A. Reference mark B indicates the relationship between the pressing depth and the pressing load for product B that was manufactured according to the same dimensional specification as product A. As was described above, the present invention reduces the effects of differences in dimensional tolerances of the components on the pressing load, which contributes to making the pressing load uniform. Products A and B are substantially similar to each other as compared to prior art products. However, in Fig. 13, a large difference between products A and B is shown for the purpose of illustration.

The above discussion does not mean that the dimensional tolerances of the components will not have any effect on the pressing load. According to precise measurements, the pressing load varies from product to product. The apparatus of Fig. 12 measures the pressing load using load cell 55D while continuing to press at the constant speed. The apparatus then cuts fine member W when the measured pressing load reaches a predetermined value. Thereafter, the apparatus keeps the pressing load constant when inner tube IN is further pressed. Consequently, all the products are adjusted to the predetermined pressing load. By utilizing such features in the assembling apparatus, in which one tube is pressed into the other tube while the pressing load is measured, and then fine member W is cut when the pressing load reaches the predetermined value, a batch of steering tubes can be assembled with high efficiency and differences in energy absorption performance

between the products also can be minimized.

The above-described assembling apparatus includes a step of extending a plurality of fine members W along the axial direction of the outer shape of inner tube IN (see Figs. 8 and 12) or the inner shape of outer tube IN (see Fig. 5) and a step of press-fitting outer tube OU around inner tube IN while prohibiting inner tube IN from directly contacting outer tube IN by means of fine members W, thereby assembling a batch of steering tubes having uniform energy absorption performance.

Each of the fine members employed in the illustrated embodiments is wound around the drum. However, in the present invention, pre-formed fine members may instead be disposed between inner tube IN and outer tube OU. Figs. 14 through 21 show examples of pre-formed fine members.

With reference to Fig. 14, first fine member W1, second fine member W2, and connection WT, which form a pair of fine members, are made from a single piece of material. In this case, two pairs are used. The other pair includes third fine member W3 and fourth fine member W4. Each connection WT is positioned on the inner end of inner tube IN and then inner tube IN is pressed into outer tube OU, or outer tube OU is press-fitted around inner tube OU.

The cross section of fine member W may be circular, because this shape can be inexpensively formed. However, when it is necessary to fit together the components such that the rigidity in the axial direction is low and the rigidity in the rotating direction is high, a variety of cross-sectional shapes can be used, as shown in Fig. 15. The fine member is not required to be solid, but also may be hollow.

Fig. 16(A) shows examples of fine members fixedly coupled to the end face of outer tube OU, in which fine members W1, W2 are disposed along the inner face of outer tube OU in the axial direction. Fine members W are connected together by connections Wf, Wc. Bent portions Wa, Wd are fixedly coupled to the end of outer tube OU in order to prohibit axial movement of the fine members. Fig. 16(B) shows another example of pre-formed fine members, in which fine members W1, W2, W3, W4 are formed from a single piece of material.

Fig. 17(A) shows another example of a pair of pre-formed fine members, in which fine members W1, W2 have different diameters. As shown in Fig. 17(B), this type of fine member is used in two pairs. Thus, inner tube IN having an oval cross-sectional outer shape may be pressed into outer tube OU having a circular cross-sectional inner shape, or inner tube IN having a circular cross-sectional outer shape may be pressed into outer tube OU having an oval cross-sectional inner shape.

Fig. 17(C) shows another example of a pair of pre-formed fine members, in which the cross-sectional shapes of the fine members are different from each other. Thus, a circular cross-sectional tube may be fitted into an oval cross-sectional tube, as shown in Fig. 17(D).

Fig. 18(A) shows another example of a pair of pre-formed fine members, in which fine members W1, W2 have different cross-sectional shapes and the cross-sectional shapes gradually change along the length of the fine member. This type of fine member may be suitably used in order to modify the energy absorption properties when energy is absorbed.

If many fine members are used, the fine members may be fixedly coupled to the tube end face one by one, as shown in Fig. 18(D). However, the fine members may instead be arranged in advance and coupled to the tube end face all at once, as shown in Fig. 18(E).

The inventors also discovered through experimentation that a coupling portion, which couples a fine member to a tube end face, may be pulled into the clearance between the tubes. This phenomenon will cause a sudden increase in the pressing load, which results in unsatisfactory energy absorption performance.

Fig. 19 through Fig. 21 show examples of pull-in prevention means provided for the coupling portions. Fig. 19(A) shows a catch portion A1 and Fig. 19(B) shows a loose portion B1. In Figs. 19(C) and (D), connections C1, C2, D1 each prevent this phenomenon. In Figs. 19(E) and (F), loops E1 and knots F1, respectively, are shown. As shown in Fig. 19(D), the lengths of fine members may be different from each other in order to impart anisotropy, in which overlapping portions of the fitted tubes are resistant to bending along the direction of long fine member L1, but tend to bend along the direction of short fine member L2. In the alternative, interspaces between adjacent fine members may be different from each other, as shown in Fig. 19(C), in order to impart anisotropy, in which overlapping portions of the fitted tubes are resistant to bending along the direction of the narrowly spaced fine members, but tend to bend along the direction of the widely spaced fine members.

Fig. 20 shows additional examples of pull-in prevention means. In Figs. 20(A) and (B), projecting

portions A1 and looped portions B1, respectively, are shown. In Fig. 20(C), connection CT includes spiral portion C1. In Fig. 20(D), other members D1, D2, D3 are threaded on fine members. Figs. 20(E) and (F) respectively show loops E1, F1. In Fig. 20(G), loops G1 are welded.

With reference to Fig. 21, an end face of an outer tube is processed to form a pull-in prevention means. As shown in Figs. 21(A) and (B), grooves for respectively receiving the fine members are formed in the end face of the outer tube in order to prevent the coupling portions from being pulled into the outer tube. Referring to Fig. 21(C), the bottom of each groove is inwardly inclined and the outer edge of the outer tube defines an acute angle. This feature also prevents the coupling portions from being pulled into the outer tube. Accordingly, an acute angle formed between the end face of the outer tube and the side thereof (or an acute angle formed between the end face of a cylindrical inner tube and the side thereof) provides the pull-in prevention effect. In addition, as shown in Fig. 21(D), this feature eliminates the need for a connection on the outer face of the outer tube (or on the inner face of the inner tube). Fig. 21(D) shows acute inner edges of the outer tube, which are examples of pull-in prevention means.

While the preferred embodiments of the present invention have been described, such description is for illustrative purposes only, and it is to be understood that changes and variations may be made without departing from the spirit or scope of the accompanying claims. The following is one preferred modification. Fine members may extend along the length of the overlapping portions of the fitted inner and outer tubes, thereby making the energy

absorption performance substantially uniform. Angular cross-sectional fine members tend to cause stress concentration and introduce plastic deformation. Accordingly, the dimensional tolerances of the components are absorbed and energy absorbing performance is made uniform. Hollow fine members also tend to cause plastic deformation. Accordingly, adverse effects of the dimensional tolerances of the components are reduced. In addition, by modifying the circumferential interspaces between adjacent fine members, rigidity can be modified as desired. Thus, axial rigidity can be adjusted. Further, even if, e.g., a weld bead remains on a circular outer tube, the fine members can be disposed so as to avoid the weld bead. This feature facilitates simple post-processing of weld beads.

Lubricant can be applied to the fine members or either one of the tubes to prevent the fine members from being pulled off when one tube is pressed into the other tube.

The above described three representative embodiments provide examples of the use of the present teachings at a position between an outer tube and an inner tube. However, the present teachings can be utilized at a position between an outer shaft and an inner shaft, in which case the inner shaft may be solid or cylindrical. The present invention can also be utilized at a position between a steering tube and a bracket, which includes a cylindrical member used to attach the steering tube to a vehicle body.

The invention of claim 1 enables the production of steering devices in which a relatively low-cost, circular cross-sectional inner shaft member is connected to a

relatively low-cost, circular cross-sectional outer tube member less rigidly to a proper degree in the axial direction and rigidly in the rotating direction. Thus, energy absorbing type steering devices can be manufactured at relatively low cost. In addition, a batch of energy absorption type steering devices can provide uniform energy absorption performance. By changing the number, the quality, the thickness, etc., of the fine members, various types of energy absorption performance can be provided.

The improvements according to claims 2 through 7 enable uniform energy absorption performance for a batch of energy absorbing type steering devices.

The assembling method according to claim 8 enables reliable assembly of a batch of steering devices having uniform energy absorption performance.

The improvements according to claims 9 to 11 further enable uniform energy absorption performance for a batch of energy absorbing type steering shafts.

The assembling apparatus according to claim 12 enables highly efficient assembly of a batch of steering devices having uniform energy absorption performance.

CLAIMS:

1. An energy absorbing type steering device, in which an outer cylindrical member is press-fitted around an inner shaft member, the steering device being characterized in that:

the outer shape of inner shaft member has a circular cross section;

the inner shape of outer cylindrical member has a circular cross section and has a diameter that is larger than the diameter of the outer shape of the inner shaft member; and

a plurality of fine members is disposed between the circular cross-sectional outer shape and the circular cross-sectional inner shape, the fine members extending along the axial direction of the inner shaft member and the outer cylinder member.

2. An energy absorbing type steering device according to claim 1, characterized in that the Vickers hardness of the inner shaft member and the Vickers hardness of the fine members differs by at least 200 or the Vickers hardness of outer cylindrical member and the Vickers hardness of the fine members differs by at least 200.

3. An energy absorbing type steering device according to any one of claims 1 and 2, characterized in that the circumferential arrangement of the plurality of fine members has been adjusted in accordance with the pressing load that is required to press-fit the outer cylindrical member around the inner shaft member.



4. An energy absorbing type steering device according to any one of claims 1 to 3, characterized in that the inner shaft member and the outer cylindrical member are fitted together with a clearance between the members, the clearance being defined at least along the length of the fine members in the axial direction.

5. An energy absorbing type steering device according to any one of claims 1 through 4, characterized in that the length of the fine members in the axial direction is longer than or equal to a predetermined length that ensures a clearance between the inner shaft member and the outer cylindrical member when the inner shaft member and the outer cylindrical member absorb energy and become more deeply fitted.

6. An energy absorbing type steering device according to any one of claims 1 through 5, characterized in that movement of the fine members in the axial direction is prohibited by fixedly coupling the fine members to an end face of the inner shaft member or to an end face of the outer cylindrical member.

7. An energy absorbing type steering device according to claim 6, characterized in that a pull-in prevention means is disposed on the end face of a coupling portion of each of the fine members.

8. A method for assembling an energy absorbing type steering device by press-fitting an outer cylindrical

member around an inner shaft member, the method being characterized by:

a step of extending a plurality of fine members along the axial direction of an outer shape of the inner shaft member or an inner shape of the outer cylindrical member; and

a step of pressing-fitting the outer cylindrical member around the inner shaft member while providing a clearance between the inner shaft member and the outer cylindrical member by means of the fine members, the clearance being defined at least along the length of the fine members that are interleaved between the members.

9. A method according to claim 8, characterized in that at least one of the inner shaft member, the outer cylindrical member, or the fine members is deformed beyond an elastic limit thereof during the pressing step.

10. A method according to any one of claims 8 and 9, further characterized by a step of measuring the pressing load being applied during the pressing step, and a step of cutting the fine members when the measured pressing load reaches a predetermined value.

11. A method according to any one of claims 8 to 10, further characterized by a step of extending a predetermined length of the plurality of fine members along the axial direction of the inner shape of the outer cylindrical member, and a step of pressing the inner shaft member while prohibiting the fine members from being axially pulled further into the outer cylindrical member.

12. An apparatus for assembling an energy absorbing type steering device being characterized by:

a device for press-fitting an outer cylindrical member around an inner shaft member; and

a fine member supply device, disposed adjacent to the pressing device, for supplying a plurality of fine members into a clearance defined between an outer shape of the inner shaft member and an inner shape of the outer cylindrical member.

13. A device according to claim 1, characterized in that the inner shaft member is an inner tube or an inner shaft, and the outer cylindrical member is an outer tube or an outer shaft.

14. A method according to claim 8, characterized in that the inner shaft member is an inner tube or an inner shaft, and the outer cylindrical member is an outer tube or an outer shaft.

15. An apparatus according to claim 12, characterized in that the inner shaft member is an inner tube or an inner shaft, and the outer cylindrical member is an outer tube or an outer shaft.

## ABSTRACT

The present invention realizes a steering device in which the dimensional tolerances of the components and variations in the finish thereof impart little adverse effects on the energy absorption performance of the device. In the energy absorption type steering device, an outer cylindrical member, or an outer tube, is press-fitted around an inner shaft member, or an inner tube. The outer shape of the inner shaft member and the inner shape of the outer cylindrical member have a circular cross section and the diameter of the inner shape of the outer cylinder member is larger than the diameter of the outer shape of the inner shaft member. A plurality of fine members is disposed along the axial direction between the circular cross-sectional outer shape and the circular cross-sectional inner shape in order to provide a clearance between the inner shaft member and the outer cylindrical member.

In the energy absorbing steering device, the inner shaft member and the outer cylindrical member each include a portion that substantially contributes to energy absorption, and the fine members prohibit the inner shaft member from directly contacting the outer cylindrical member at least in this portion. Thus, the energy absorption performance is less susceptible to the effects of dimensional tolerances of the inner shaft member and outer tube member and variations in the finish thereof. Accordingly, a robust technique is achieved.

FIG.1





FIG.2



2/17

FIG.3






FIG.4



**FIG.5**



4/17

FIG.6




FIG.7








FIG.8



10/C69308

6/17

FIG.9



7/17

FIG.10






FIG.11



8/17

FIG.12



10/069398

9/17

FIG.13





FIG.14




10/17

FIG.15




FIG.16




11/17

FIG.17



12/17

FIG.18





13/17

FIG.19







FIG.20



15/17


FIG.21





17/17

FIG.23



Japanese Language Declaration  
(日本語宣誓書)

私は、米国法典第 35 編 119 条 (a)-(d) 項又は 365 条 (b) 項に  
基き、下記の米国以外の国の少なくとも一カ国を指定している特  
許協力条約 365 (a) 項に基く国際出願、又は外国での特許出願も  
しくは発明者証の出願についての外国優先権をここに主張する  
とともに、優先権を主張している、本出願の前に出願された特許ま  
たは発明者証の外国出願を以下に、枠内をマークすることで、示  
しています。

Prior Foreign Application(s)

外国での先行出願

11-239399	Japan
(Number)	(Country)
(番号)	(国名)
PCT/JP00/02922	Japan
(Number)	(Country)
(番号)	(国名)
PCT/JP00/05137	Japan
(Number)	(Country)
(番号)	(国名)

私は、下記の米国法典第 35 編 120 条に基づいて下記の米国特  
許出願に記載された権利、又は米国を指定している特許協力条  
約 365 条に基づく権利をここに主張します。また、本出願の各請  
求範囲の内容が米国法典第 35 編 112 条第 1 項又は特許協力条約  
で規定された方法で先行する米国特許出願に開示されていない  
限り、その先行米国出願書提出日以降で本出願書の日本国内ま  
たは特許協力条約国際提出日までの期間中に入手された、連邦  
規則法典第 37 編 1 条 56 項で定義された特許資格の有無に関す  
る重要な情報について開示義務があることを認識しています。

I hereby claim foreign priority under Title 35, United States Code,  
Section 119, (a)-(d) or 365(b) of any foreign application (s) for  
patent or inventor's certificate, or Section 365(a) of any PCT  
international application which designated at least one country  
other than the United States, listed below and have also  
identified below, by checking the box, any foreign application for  
patent or inventor's certificate, or PCT International application  
having a filing date before that of the application on which  
priority is claimed.

Priority Claimed  
優先権主張

26/08/1999	<input checked="" type="checkbox"/> <input type="checkbox"/>
(Day/Month/Year Filed)	Yes No
(出願年月日)	はい いいえ
01/05/2000	<input checked="" type="checkbox"/> <input type="checkbox"/>
(Day/Month/Year Filed)	Yes No
(出願年月日)	はい いいえ
28/07/2000	<input checked="" type="checkbox"/> <input type="checkbox"/>
(Day/Month/Year Filed)	Yes No
(出願年月日)	はい いいえ

I hereby claim the benefit under Title 35, United States  
Code, Section 120 of any United States (s), or Section 365(c) of  
any PCT International application designating the United States,  
listed below and, insofar as the subject matter of each of the  
claims of this application is not disclosed in the prior United  
States or PCT International application in the manner provided by  
the first paragraph of Title 35, United States code Section 112, I  
acknowledge the duty to disclose Information which is material to  
patentability as defined in Title 37, Code of Federal Regulations,  
Section 1.56 which became available between the filing date of the  
prior application and the national or PCT International filing date  
of application.

(Application No.)	(Filing Date)
(出願番号)	(出願日)

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)

(Application No.)	(Filing Date)
(出願番号)	(出願日)

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)

私は、私自身の知識に基づいて、本宣誓書中で私が行う表明が  
真実であり、かつ私の入手した情報と私の信じるところに基づ  
く表明が全て真実であると信じていること、さらに故意になさ  
れた虚偽の表明及びそれと同等の行為は米国法典第 18 編第  
1001 条に基づき、罰金または拘禁、もしくはその両方によ  
り処罰されること、そしてそのような虚偽の声明を行えば、出  
願した、又は既に許可された特許の有効性が失われることを認  
識し、よってここに上記のごとく宣誓をいたします。

I hereby declare that all statements made herein of my own  
knowledge are true and that all statements made on information  
and belief are believed to be true; and further that these  
statements were made with the knowledge that willful false  
statements and the like so made are punishable by fine or  
imprisonment, or both, under Section 1001 of Title 18 of the  
United States Code and that such willful false statements may  
jeopardize the validity of the application or any patent issued  
thereon.

Japanese Language Declaration  
(日本語宣誓書)

委任状：私は下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁理士として、下記の登録番号を付された Kenyon & Kenyon 事務所の弁理士を指名いたします。

POWER OF ATTORNEY: As a named inventor, I hereby appoint the registered practitioners of Kenyon & Kenyon included in the customer Number provided below to prosecute this application and transact all business in the Patent and Trademark Office connected therewith:

KENYON & KENYON (23838)

書類送付先

Send Correspondence to:

Please address all correspondence to the above Customer Number.

直接電話連絡先：(名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

(202) 220-4200

唯一または第一発明者名	Full name of sole or first inventor Shigemi SHIOYA
発明者の署名 日付	Inventor's signature Date Shigemi Shioya March 21, 2002
住所	Residence c/o TOYOTA JIDOSHA KABUSHIKI KAISHA JPX 1, Toyotacho, Toyota-shi, Aichi, 471-8572 Japan
国籍	Citizenship Japanese
郵便の宛先	Post Office Address c/o TOYOTA JIDOSHA KABUSHIKI KAISHA 1, Toyotacho, Toyota-shi, Aichi, 471-8572 Japan

第二共同発明者名	Full name of second joint inventor, if any Sadato KITA
第二共同発明者の署名 日付	Second Inventor's signature Date Sadato Kita March 25, 2002
住所	Residence c/o TOYOTA JIDOSHA KABUSHIKI KAISHA JPX 1, Toyotacho, Toyota-shi, Aichi, 471-8572 Japan
国籍	Citizenship Japanese
郵便の宛先	Post Office Address c/o TOYOTA JIDOSHA KABUSHIKI KAISHA 1, Toyotacho, Toyota-shi, Aichi, 471-8572 Japan

(第三以降の共同発明者についても同様に記載し、署名すること)

(Supply similar information and signature for third and subsequent joint inventors.)

# Japanese Language Declaration

第三共同発明者名	Full name of third joint inventor, if any <u>Takashi SHIMADA</u>	
第三共同発明者の署名	日付	Third Inventor's signature <u>Takashi Shimada</u> Date <u>March 27, 2002</u>
住所	Residence c/o TOYOTA JIDOSHA KABUSHIKI KAISHA 1, Toyotacho, Toyota-shi, Aichi, 471-8572 Japan <u>JPX</u>	
国籍	Citizenship Japanese	
郵便の宛先	Post Office Address c/o TOYOTA JIDOSHA KABUSHIKI KAISHA 1, Toyotacho, Toyota-shi, Aichi, 471-8572 Japan	

第四共同発明者名	Full name of fourth joint inventor, if any <u>Seiji SANO</u>	
第四共同発明者の署名	日付	Fourth Inventor's signature <u>Seiji Sano</u> Date <u>March 28, 2002</u>
住所	Residence c/o TOYOTA JIDOSHA KABUSHIKI KAISHA 1, Toyotacho, Toyota-shi, Aichi, 471-8572 Japan	
国籍	Citizenship Japanese <u>JPX</u>	
郵便の宛先	Post Office Address c/o TOYOTA JIDOSHA KABUSHIKI KAISHA 1, Toyotacho, Toyota-shi, Aichi, 471-8572 Japan	

第五共同発明者名	Full name of fifth joint inventor, if any	
第五共同発明者の署名	日付	Fifth Inventor's signature Date
住所	Residence	
国籍	Citizenship	
郵便の宛先	Post Office Address	


第六共同発明者名	Full name of sixth joint inventor, if any	
第六共同発明者の署名	日付	Sixth Inventor's signature Date
住所	Residence	
国籍	Citizenship	
郵便の宛先	Post Office Address	

(第七またはそれ以降の共同発明者に対しても同様な  
情報および署名を提供すること。)

(Supply similar information and signature for seventh and  
subsequent joint inventors.)



United States Patent & Trademark Office  
Office of Initial Patent Examination -- Scanning Division



Application deficiencies found during scanning:

☒ Page(s) 1 of 4 of Declaration <sup>was</sup> ~~were~~ not present  
for scanning. (Document title)

☐ Page(s) \_\_\_\_\_ of \_\_\_\_\_ were not present  
for scanning. (Document title)

☐ *Scanned copy is best available.*